



1757 Burlington St. E.

Hamilton, ON L8N 3R5

PH: 905-548-9604 / 1-800-561-9931

FX: 905-547-0113

[www.clowcanada.com](http://www.clowcanada.com)

## KENNEDY /CLOW ULC/FM 2945A INDICATOR POSTS & INDICATOR POST VALVES STANDARD STOCK MODELS / BURY DEPTHS & GENERAL INFORMATION

MODEL 2945A : The length of bury is the distance measured to the nearest half foot from the bottom of the connecting pipe to the finished grade.

### McAVITY POST INDICATORS

#### MODEL 2945A Weight Lbs

| BURY CODE   | B                               | C                               | D                               | E                               |
|---|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
| KENNEDY 2945A (BURY RANGE B THROUGH E) TELESCOPING INDICATOR POST (3 - 14" valve) ULC/ FM approved - 60 TURNS MAXIMUM |                                 |                                 |                                 |                                 |
| <b>WEIGHT &amp; LENGTH</b>  | 160 lbs / 71" long              | 190 lbs / 89" long              | 219 lbs / 107" long             | 265 lbs / 137" long             |
| <b>size</b>   | <b>bury range (ft / metres)</b> | <b>bury range (ft / metres)</b> | <b>bury range (ft / metres)</b> | <b>bury range (ft / metres)</b> |
| 3"  | 2'5"-4'1" / 0.76-1.25           | 3'8"-5'6" / 1.16-1.7            | 5'4"-7' / 1.64-2.13             | 7'4"-9'4" / 2.25-2.86           |
| 4"  | 2'7"- 4'3" / 0.79-1.30          | 4'0"- 5'8" / 1.23- 1.73         | 5'6"- 7'2" / 1.68- 2.18         | 7'6"- 9'6" / 2.29-2.9           |
| 6"  | 2'11"- 4'7" / 0.89-1.40         | 4'5"- 6'1" / 1.32- 1.85         | 5'11"- 7'7" / 1.80- 2.31        | 7'11"- 9'11" / 2.41- 3.02       |
| 8"  | 3'4"- 5'0" / 1.02-1.52          | 4'10"- 6'6" / 1.47- 1.98        | 6'4"- 8'0" / 1.93- 2.44         | 8'4"-10'4" / 2.54-3.15          |
| 10"   | 3'9"- 5'5" / 1.14-1.65          | 5'3"- 6'11" / 1.60- 2.12        | 6'9"- 8'5" / 1.60- 2.57         | 8'9"- 10'8" / 2.67-3.25         |
| 12"   | 4'1"- 5'9" / 1.24-1.75          | 5'7"- 7'3" / 1.70- 2.21         | 7'1"- 8'9" / 2.16- 2.67         | 9'1"- 11'1" / 2.77-3.38         |
| 14"   | 4'10"-6'6" / 1.47-1.98          | 6'4"-8'0" / 1.93-2.44           | 7'10"-9'6" / 2.39-2.89          | 9'10"-11'10" / 2.99-3.6         |

INDICATOR POST VALVES /AWWA C509 3 - 12 AWWA C515 14 & LARGER /DUCTILE IRON or CAST IRON CLASS 125 , FLANGED, FF ANSI B16.1(all standard end connections available)/ ULC& FM APPROVED 3- 16" Dia./ EPOXY COATED ULC/FM RATED TO 200 PSI WWP

#### Post Indicator Valves

| SIZE | PIV CAST & DUCTILE IRON - TURNS TO FULL | WEIGHT |
|------|---|--------|
| 3"   | 10.00                                   | 78     |
| 4"   | 13.50                                   | 103    |
| 6"   | 19.50                                   | 150    |
| 8"   | 25.50                                   | 228    |
| 10"  | 31.50                                   | 385    |
| 12"  | 37.75                                   | 539    |
| 14"  | 52.00                                   | 700    |

\*\* Weight is for Flange Valves - other styles weight may be + or - 5%

\*\* NOTE: 16" & LARGER VALVES USE 2945A HD OR HDG INDICATOR POST